



Corning InfiniBeam® expanded beam connectors provide the ultimate in reliable performance in harsh environments where water, mud, dust and fluid exposure are a concern. Utilizing expanded beam technology, the design and packaging of these connectors provide a robust connectivity solution resistant to corrosion, mechanical and thermal shock while inherently providing easy field cleaning. Available in a variety of configurations, number of channels and sizes, some of the applications suitable for STRAN's expanded beam technology include:

- Oil and Gas surface applications
- Deployable military tactical systems
- Video/data transmission
- Homeland security and surveillance
- Outside Broadcast
- Underground and surface mining operations

## Features and Benefits

Expanded beam inserts that expand the signal 200x reducing the effect of dust, dirt and other contaminants on the optical path

Multiple plating options: Hard Anodize (Clear, Dark Green or Bronze) and Molded Rubber Grip on plug connector

4 & 12 channel options for plug and receptacle

Easy field cleaning without tools


Hermaphroditic interface

Custom deployment reels for plug to plug assemblies

Available for all fiber types and sizes

ISO9001-2000 since '03 and AS9100B since

## InfiniBeam® Expanded Beam Fiber Optic Connector Dimensions



## Technical and Performance Characteristics

Optical Insertion Loss	62.5/125 $\mu$ m: 1.5 dBmax, 1.0 dBtyp @850nm and 1300nm
Mating Durability	3000 cycles per EIA-455-21
Corrosion Resistance	EIA-455-16, salt spray, test condition C
Temperature/Humidity	-10° C to +65° C, 10 cycles per EIA-455-5 method B
Physical Shock	EIA-455-14 condition C
Temperature Cycle	-46°C to +71°C, 5 cycles
Temperature Life	85°C for 250 hours per EIA 455-4
Vibration	EIA-455-11 condition III at 10g, condition VI C for 1.5hrs
Cable Retention	> 400Lbs per EIA 455-6
Temperature	-46°C to +85°C operating -52°C to +85°C storage
Impact	EIA-455-2, method C, severe
Crush	EIA-455-26, 6.7kN (1,506lbf)
Thermal Shock	EIA-455-71, schedule C, 10 cycles, 85°C to -57°C



CORNING

Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC 28216 USA  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

Corning Optical Communications reserves the right to improve, enhance, and modify the features and specifications of Corning Optical Communications products without prior notification. A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved.