		NITH INTEGRATED CABLE GUIDE, IMP GROUNDED TO OUTER SHELL.	- OPTIONAL HIGH INTEGRITY GROUNDING RING				01	PRELIN
	SHIELDING AND CABLE CRI FOR USE WITH AWG24/26	CABLE 0,94 - 1,07Ø OVER INSULATION.					LI	
	2134		O RING SEAL					
			CABLE SHOWN FOR CLARITY ONLY					
			CABLE SEALING RANGE 6,70±0.50					
			CABLE SEALING RANGE 6, $70 \pm 0,50$					
	OPTION X (STANDARD)	LASER PART/BATCH						
		MARK HERE						
		43,00 MAX						
			18,00					
			Ø15,56					
			BT TERMINATION OPTION					
			ORDER BAND SEPARATELY					
\geq	OPTION W OPTION	Y OPTION Z						
	OF HON W OP HON							
	CODE 1-C	MATERIAL / PLATING ALUMINIUM / ELECTROLESS NICKEL						
	1-B ALUMI	NIUM / CADMIUM OLIVE DRAB OVER ELECTROLES IUM / ZINC COBALT OLIVE DRAB OVER ELECTROLE						
	4-J	STAINLESS STEEL / PASSIVATE						
	2-Z LIST NOT EXHAUS	NICKEL ALUMINIUM BRONZE / SHOT BLAST STIVE, FOR COMPREHENSIVE LIST AND SPECS, SE						
		,						
			ST4D0024(BT)-19NX-1-C(-H)					
	NOTES					TOLERANCE	S DRAWN BY M. DEC	CARLO (
	GENERALLY TO THE REQUIREMENTS OF MIL-DTL-38999 MATES WITH AMPHENOL RJFTV					.0	CHECKED BY	
	FINISH SEE TABLE	TERMINATION STYLE (OMIT FC SHELL SIZE				.00		
	MATERIALS RJ45	KEY ARRANGEMENT (N, A, B, C,	, D, E)			.000	APPROVED BY	D/
	CONTACTS SELECTIVE GOLD PLATING SHIELDING - NICKEL PLATED BRASS	INSERT ROTATION (W, X, Y, Z) -				ANGLES ± - 1.0)°	
	BODY - PBT, UL94V-0	MATERIAL (SEE TABLE)					wise specified all di	IMENSIONS ARE IN
	SEAL - SILICONE ELASTOMER						DIMENSIONS APPLY	
	PERFORMANCE VOLTAGE RATING 50V DC / 35V AC	HIGH INTEGRITY GROUNDING					ROPRIETARY INE	
	TEMPERATURE 40°C TO +120°C	PART NUMBER FOR UNGROUNDE	D VERSION: ST4D0024-19NX-1-C-U			EXPRE	UMENT CONTAINS PROP IN TECHNOLOGIES AND ISSED CONDITIONS THAT	IT IS NOT TO BE DIS-
						CLOSED C FOR MAN	OR REPRODUCED IN WH UFACTURING FOR ANYC	OLE OR PART, OR US
						THAT NO	DLOGIES WITHOUT ITS WE D RIGHT IS GRANTED TO ORMATION CONTAINED	DISCLOSE OR SO US
							THIRD ANGLE PROJ	
				NEXT ASS'Y	USED ON		\oplus =	
				APPLI	CATION		ψ \sim	
				\wedge				CAGE CO

– RJ45 CAT6a (10Gb) PLUG WITH INTEGRATED CABLE GUIDE, SHIELDING AND CABLE CRIMP GROUNDED TO OUTER SHELL. FOR USE WITH AWG24/26 CABLE 0,94 - 1,07Ø OVER INSULATION.

	PART. NO.	00-06	502	^{sн}]	REV.		
		evisions		BY	DATE	APVD.]
P	RELIMINARY RELEA	SE		MGD	09/18/13		
)	DATE 09/18/13						PART NO.
, 	DATE	\bigcirc	str	ΠD	NAUGATUC	NT HILL RD CK, CT 06770	00
	DATE		ТЕСНКО	LOGIES	(203) /	20-6500	0-0
15 4		TITLE	CON	INI A'	Y'22		900-0602
atin Lon		_		6a R			\sim
IFOR ED (O BE	RMATION ON THE E DIS-			PLUG	510		SH
NRT, O THANSEN OR S	OR USED N STRAN IT AND SO USE						
oci	JMENT.	DWG. SIZE	PART NO.			REV.	01
		В	90	0-06		01	
CAG	GE CODE: 1HVU5	SCALE	NONE CUSTOME		SHEET 1 OF		
				, UUL L	×1\7 \ 7 ¥		

REV.

01

SCN NO.